

#### 8600

AudioVideo power supply stabilized with timer cabling Traditional.

Supply: 230 V a.c., 35 VA.
Outputs: 16 V a.c., 12 V d.c., 18 V d.c.
Dimensions: 185x100x77 mm.

(10,5 DIN modules).

#### 8604

AudioVideo additional power supply, cabling Traditional and Simplified to connect monitors with Image Memory in multi users systems. Supply: 230 V a.c., 35 VA, Outputs: 18 V d.c., 1 A.

Dimensions: 185x100x77 mm. (10,5 DIN modules).



### 8843

AudioVideo automatic switch cabling Traditional. For Video systems with 2 main video entrance panels or with 1 main and more stairs video entrance panels. Inputs: 18 V d.c. Dimensions: 185x100x77 mm. (10,5 DIN modules).

## **ACCESSORIES**



## 2052/E

Audio amplified speaker unit cabling Traditional, with embedded electronic call and call tone feedback. Speech volume adjustment.



## 8050

B/W CCD camera 1/3", lens f.2,0/3,6 mm, 6 IR LEDS for night vision, cabling Traditional, Video outputs signal on coax cable. Suplly: 18 V d.c.

## 8050/C

Colour CCD camera 1/4", lens f.3/2,8 mm, cabling Traditional. Video outputs signal on coax cable. Supply: 18 V d.c.



#### 853

Additional external piezoelectric buzzer. Supply: 15 V a.c./d.c.

# 853/1

External passive call repeater. To connect in systems with electronic call. Supply: 15 V a.c./d.c.



## 859/20

Interface relay with 1 contact 2NO-2NC. Supply: 12÷24 V a.c./d.c. Dimensions: 70x86x71 mm. (3 DIN modules).

#### 859/21

Interface relay with 2 contacts 2NO-2NC + 2NO-2NC.

Supply: 12÷24 V a.c./d.c.

Dimensions: 70x86x71 mm. (3 DIN modules).



Active Video ditributor 4 outputs cabling Traditional, for video systems with coax cable. Amplification: 1 db. Supply: 18 V d.c.

Dimensions: 73x77x26 mm.



## SUO/V

Additional buzzer cabling Traditional and Simplified.

Can be fitted inside the telephone "ELITE".

Supply: 12/15 V a.c.

#### SUO/E

Additional tone generator cabling Traditional and for telephone "ELITE PLUS" with more than 3 telephone in parallel.

Can be fitted inside the telephone "ELITE".