

# Online UPS, 1000 VA

## EG-UPS0-1000

### ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



### Características

- Online type UPS: double voltage conversion without switching the power
- USB control interface
- LCD display
- Short circuit protection
- Compatible with power generators of any brand
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

### Embalaje

Cantidad por caja, pcs	1
Volumen caja, mc	0.0320256
Peso caja, kgs	10.6
Medidas cajas individuales LxWxH:	400x240x320 mm
Medidas caja LxWxH	417x240x320 mm
Pais de origen	CN
Código de barras	8716309124836
codigo de aduanas	8504408590

### Contenido de la caja

- UPS
- Power cord
- USB cable
- Software CD
- Spare fuse

### Certificados



### Especificaciones

UPS type: online, pure sine wave  
 Input: 220V AC  $\pm$  25%, 50Hz / 60Hz  $\pm$  10%  
 Output: 220V AC  $\pm$  1%, 50Hz / 60Hz  $\pm$  0.5% (on battery)  
 Output power factor: > 0.99  
 Inverter output efficiency (resistive load): 85%, any load type is allowed

Switching time: zero  
 Backup time: 8...20 mins (depends on the load)  
 Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 9 Ah / 2.35 kg x 2 pcs, 24VDC  
 Charge time: 90% capacity restored in 3 hours  
 External battery connectors: yes  
 Sockets: input IEC C14, outputs: 1x schuko sockets + 3x IEC sockets

Interface communication: USB; optional slots: RS485 / dry contacts / SNMP

Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Noise: < 45 dB (at 1 meter distance)  
 Power: 1000 VA (900 W)  
 Dimensions: 144 x 312 x 216 mm  
 Product weight: 11 kg  
 "Cold-start" function

### Requisitos del sistema

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.