



GLOBAL



Shelly 2PM Gen3



Power supply 110-240 V~ / 24 V=

Max load 16 A (240 V~);
10 A (30 V=)

Power metering Yes

Connectivity Wi-Fi 4
Bluetooth 4.2

CPU ESP-Shelly-C38F

Flash Memory 8 MB

Size (HxWxD) 37x42x16 mm /
1.46x1.65x0.63 in

Weight 30 g / 1.06 oz

Certifications RED, LVD, EMC, CE, RCM

[more info →](#)



GLOBAL



Shelly 2PM Gen4



Power supply 110-240 V~ / 24 V=

Max load 16 A (240 V~);
10 A (30 V=)

Power metering Yes

Connectivity Wi-Fi 6
Bluetooth 5.0

CPU ESP-Shelly-C68F

Flash Memory 8 MB

Size (HxWxD) 37x42x16 mm /
1.46x1.65x0.63 in

Weight 30 g / 1.06 oz

Certifications RED, LVD, EMC, CE, RCM

[more info →](#)



EU

US

ANZ



Shelly Wave 2PM



Power supply EU: 110-240 V~ / 24 V=
ANZ: 110-240 V~
US: 120 V~

Max load EU/ANZ: 10 A/channel,
16 A total (240 V~)
EU: 10 A (30 V=)
US: 7 A per channel,
14 A total (120 V~)

Power metering Yes

Connectivity ZWLR EU: 864 MHz
US: 912 MHz
Z-Wave Plus

EU: 868.4 MHz
US: 908.4 MHz
ANZ: 919.8 MHz
Z-Wave® S800

CPU

Size (HxWxD) 37x42x16 mm /
1.46x1.65x0.63 in

Weight 29 g / 1.02 oz

Certifications RED, LVD, EMC, CE, RCM,
FCC, SA, UL

[more info →](#)

