# 2-CHANNEL RELAYS WITH POWER METERING

GLOBAL

Shelly
## 2PM Gen3

| | |
|---|---|
| Power supply | 110-240 V~ / 24 V⎓ |
| Max load | 16 A (240 V~);<br>10 A (30 V⎓) |
| Power metering | Yes |
| Connectivity | Wi-Fi 4<br>Bluetooth 4.2 |
| CPU | ESP-Shelly-C38F |
| Flash Memory | 8 MB |
| Size (HxWxD) | 37x42x16 mm /<br>1.46x1.65x0.63 in |
| Weight | 30 g / 1.06 oz |
| Certifications | RED, LVD, EMC, CE, RCM |

more info →

GLOBAL

Shelly
## 2PM Gen4

| | |
|---|---|
| Power supply | 110-240 V~ / 24 V⎓ |
| Max load | 16 A (240 V~);<br>10 A (30 V⎓) |
| Power metering | Yes |
| Connectivity | Wi-Fi 6<br>Bluetooth 5.0 |
| CPU | ESP-Shelly-C68F |
| Flash Memory | 8 MB |
| Size (HxWxD) | 37x42x16 mm /<br>1.46x1.65x0.63 in |
| Weight | 30 g / 1.06 oz |
| Certifications | RED, LVD, EMC, CE, RCM |

more info →

EU
US
ANZ

Shelly
## Wave 2PM

| | |
|---|---|
| Power supply | EU: 110-240 V~ / 24 V ⎓<br>ANZ: 110-240 V ~<br>US: 120 V~ |
| Max load | EU/ANZ: 10 A/channel,<br>16 A total (240 V~)<br>EU: 10 A (30 V⎓)<br>US: 7 A per channel,<br>14 A total (120 V~) |
| Power metering | Yes |
| Connectivity | ZWLR EU: 864 MHz<br>US: 912 MHz<br>Z-Wave Plus<br>EU: 868.4 MHz<br>US: 908.4 MHz<br>ANZ: 919.8 MHz |
| CPU | Z-Wave® S800 |
| Size (HxWxD) | 37x42x16 mm /<br>1.46x1.65x0.63 in |
| Weight | 29 g / 1,02 oz |
| Certifications | RED, LVD, EMC, CE, RCM,<br>FCC, SA,UL |

more info →