

2 CHANNEL RELAYS



GLOBAL



Shelly
PRO 2PM



Power supply 110-240 V~

Max load 16 A per channel,
25 A total /
12.5 A UL Version

Power metering Yes

Connectivity Wi-Fi 4
Bluetooth 4.2
LAN

CPU ESP32-D0WDQ6

Flash Memory 8 MB

Size (HxWxD) 94x19x69 mm /
3.70x0.75x2.71 in

Weight 76 g / 2.68 oz

Certifications RED, LVD, EMC, CE,
UL, RCM



[more info →](#)

EU

US

ANZ



Shelly
Wave PRO 2PM



Power supply 110-240 V~

Max load EU/ANZ: 16 A/channel,
25 A total;
US: 12.5 A per channel,
25 A total;

Power metering Yes

Connectivity ZWLR

EU: 864 MHz
US: 912 MHz
Z-Wave Plus
EU: 868.4 MHz
US: 908.4 MHz
ANZ: 919.8 MHz
Z-Wave® S800

CPU

Size (HxWxD) 94x19x69 mm /
3.70x0.75x2.71 in

Weight 73 g / 2.58 oz.

Certifications RED, LVD, EMC, CE,
RCM, FCC, SA



[more info →](#)

EU

US

ANZ



Shelly
Wave PRO Shutter



Power supply EU: 110-240 V~
US: 120 V~
ANZ: 110-240 V~

Max load EU/ANZ: 16 A/channel
US: 12.5 A/channel

Connectivity ZWLR

EU: 864 MHz
US: 912 MHz
Z-Wave Plus
EU: 868.4 MHz
US: 908.4 MHz
ANZ: 919.8 MHz
Z-Wave® S800

CPU

Size (HxWxD) 94x19x69 ± 0.5 mm /
3.70x0.75x2.71 ± 0.02 in

Weight 75 g / 2.65 oz.

Certifications RED, LVD, EMC, CE, RCM,
FCC, SA



[more info →](#)