

ECMA2010

MINITRUNKING HINGED LID AND SELF-ADHES. BOTTOM 20X10

Canalizaciones > Pared y techo > Minicanales > Serie ma - cintas adhesivas de doble cara con tapa integrada > Minicanales > Blanco

Technical Symbols/Marks/Approvals

IP40 | IK04 | UL94 V0 | GWT 960° | CE | RoHS II | MADE IN ITALY

Estándares

EN 50085-1 EN 50085-2-1

Descripción

Minicanal fabricado en tecnopolímero a base de PVC rígido autoextinguible. Con cintas adhesiva de doble cara para. Tapa integrada con cierre a presión.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000059 - Mini/maxi trunking

Degree of protection (IP)	IP40	**Material**	Plastic	**Material quality**	Polyvinyl chloride (PVC)
Halogen free	No	**Anti-bacterial treatment**	No	**Surface protection**	Untreated
Colour	White	**Transparent**	No	**Impact strength**	IK04
Type of fastening	Self-adhesive	**Width**	20 mm	**Height**	10 mm
Length	2000 mm	**Usable cross section**	128 mm²	**RAL-number**	9001
With protective foil	No	**Working temperature**	-5 ÷ 60 °C	**Cover model**	With film hinge
Suitable for circuit integrity	No	**Number of permanent partitions**	0	**Number of plug-in partitions**	0
With cable fixing clip	No	**With duct connector**	No	**Delivery on roll**	No
Pre-stamping	No				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8054320282358

Cardboard

100 MT

0.195x0.102x2.025 [m]

9.5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.