


300Mbps Wireless N Router

N300 with Proven Stability










Features







Reliability

- · Wireless N Speed 300Mbps Wi-Fi speed meets your daily internet needs
- · 802.11n Backward compatible with 802.11b/g products
- · MIMO Technology 2 x 2 MIMO technology increases efficiency for streaming & gaming
- · Easy Bandwidth Management Bandwidth Control allocates necessary speed of each connected device to ensure quality of multimedia streaming

Ease of Use

- · Intuitive Web UI- Ensures quick and simple installation without hassle
- · Fast Encryption One-touch WPA wireless security encryption with the WPS button


Security

- · Access Control Establish a whitelist or blacklist to allow or block certain devices from accessing the internet
- Parental Controls Manage when and how children devices can access the internet
- · Encryptions for Secure Network WPA-PSK/WPA2- PSK encryptions provide active protection against security threats

Specifications

Hardware

- · Ethernet Ports: 4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port
- · Buttons: WPS/Reset Button
- · Antennas: 2 fixed Omni Directional Antennas
- · External Power Supply: 9VDC / 0.6A
- · Dimensions (W x D x H): 7.2 x 5.0 x 1.4 in. (182 x 128 x 35mm)



LAN

Desktop

Game Console



Wireless

- · Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
- · Frequency: 2.4-2.4835GHz
- · Signal Rate:

11n: Up to 300Mbps(dynamic)

11g: Up to 54Mbps(dynamic)

11b: Up to 11Mbps(dynamic)

· Reception Sensitivity:

270M: -68dBm@10% PER

130M: -71dBm@10% PER

108M: -72dBm@10% PER

54M: -74dBm@10% PER

11M: -86dBm@8% PER

6M: -86dBm@10% PER

1M: -94dBm@8% PER

- Wireless Function: Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
- · Wireless Security: WEP, WPA / WPA2, WPA-PSK / WPA2-PSK

Specifications

Software

- · Working Modes: Wireless Router, Access Point
- · WAN Type: Dynamic IP/Static IP/PPPoE/PPTP/L2TP(Multi-EWAN)
- · DHCP: Server, DHCP Client List, Address Reservation
- · Quality of Service: WMM, Bandwidth Control
- · Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ
- · Dynamic DNS: DynDns, Comexe, NO-IP
- · Access Control: Parental Controls, Local Management Control, Host list, Access Schedule, Rule Management
- · Firewall Security: DoS, SPI Firewall, IP and MAC Address Binding
- · Protocols: IPv4, IPv6
- Management: Access Control, Local Management, Remote Management, TR-069

Others

· Certification

CE, FCC, RoHS

· System Requirements

Microsoft Windows 10/8.1/8/7/Vista/XP/2000/NT/98SE, MAC OS, NetWare, UNIX or Linux

Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser

Cable or DSL Modem

Subscription with an internet service provider (for internet access)

Environment

Operating Temperature: 0°C~40°C (32°F ~104°F)

Storage Temperature: -40°C~70°C (-40°F ~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Package Contents

300Mbps Wireless N Router TL-WR850N

Power Adapter

RJ-45 Ethernet Cable

Quick Installation Guide

www.tp-link.com ©2018 TP-Link 300Mbps Wireless N Router TL-WR850N