

# HWN-2104MH-W

NVR for IP cameras with WiFi module

4 CH video

Max Resolution 4.0 Mpx /

Compression H.265+

Bandwidth 40 Mbps

Full HD HDMI and VGA Output

Supports 1 hard disk



Hikvision HiWatch Series

NVR for IP cameras

4 CH

WiFi module (allows to connect the cameras by WiFi and connects to the local network by UTP cable)

40 Mbps bandwidth supported

Maximum resolution 4 Megapixel

Compression H.265+/H.265/H.264+/H.264

Full HD HDMI and VGA Output

IP Dual Stream Access

Mouse

Space for 1 HDD

WEB, CMS and Smartphone interface

ONVIF Compatible

# Specifications

<b>Brand</b>	Hikvision
<b>Range</b>	HiWatch Series
<b>Inputs for IP cameras</b>	LAN port up to 4 channels
<b>IP compatible cameras</b>	HIKVISION, ONVIF
<b>Bidirectional audio</b>	1 input / 1 RCA output
<b>Video outputs</b>	1 HDMI Full HD, 1 VGA
<b>Video compression format</b>	H.265+ / H.265 / H.264+ / H.264
<b>Display resolution</b>	1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
<b>Total bandwidth</b>	40 Mbps downstream / 60 Mbps upstream
<b>Main Stream recording</b>	4MP/3MP/1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF
<b>Decoding capacity</b>	1CH@4Mpx or 2CH@1080p
<b>Simultaneous multifunction</b>	Pentaplex: Live, Recording, Playback, Backup and Remote Access
<b>Alarms</b>	No
<b>Recording method</b>	Manual, programmed, motion detection, alarm
<b>External Backup</b>	USB memory / HDD USB / CD-RW USB / DVR-RW USB
<b>Internal memory</b>	1 SATA HDD 3.5" of up to 6 TB (not included)
<b>Communication</b>	2 x USB 2.0 / 1 x RJ45 10/100/1000 (Ethernet) / WiFi Module for communication
<b>Remote access</b>	Web Browser, Smartphone App IVMS 4500 and PC Software IVMS 4200
<b>Power supply</b>	DC 12 V, 50/60 Hz
<b>Dimensions / Weight</b>	48 (H) x 315 (W) x 240 (D) mm / 1.0 Kg (without HDD)